

2018 OUTLANDER™ 6x6 DPS™ 650

HIGHLIGHTS

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg capacity Dual-Level™ cargo box with modular accessories
- 750 kg towing capacity
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Double A-arm front suspension with dive-control geometry
- 12-in. cast-aluminum wheels
- Relocated air intakes
- Quick release sway bar
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- RF Digitally Encoded Security System (D.E.S.S.™)



Green

ENGINE

650

Type	62 hp, Rotax 649.6 cc V-twin liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 23.6 cm travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS

Front Tires	Carlisle Badland 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Badland 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	312 x 124 x 126 cm
Wheelbase	208.1 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Dry Weight	489 kg
Rack Capacity	Front: 45 kg Rear: 318 kg
Storage Capacity	Dual-level cargo box with modular accessories Rear: 70 L
Towing Capacity	750 kg
Fuel Capacity	20.5 L

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Protection	N/A	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY

Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage

BEST PROTECTION ©2017 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GMV Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am



Can-AmOffroad.com