Sefender XT

IIGHLIGHTS

- Heavy-duty Rotax® V-Twin engine
- PRO-TORQ transmission
- Dynamic Power Steering (DPS[™])
- Lockable rear differential and Visco-Lok[‡] QE • auto-locking front differential
- TTA-HD rear suspension

Not EC homologated

- 14-in. (35.6 cm) Black cast-aluminum wheels with • 27-in. (68.6 cm) Maxxis Bighorn 2.0⁺ tires
- EC0[™] / Work / Normal driving modes 16.2 gal (61.3 L) of storage capacity including 1.7 gal (6.3 L) water-resistant toolbox and 5.6 gal (21 L) waterproof under passenger seat storage box
- VERSA-PRO bench seat with reinforced XT seat skin and adjustable driver seat
- Multifunction cargo box with sturdy tailgate •
- . 4,500-lb (2,014 kg) winch
- Full hard roof •
- . Full skid plate
- Multifunction analog / digital gauge • 1-year maintenance free and easy access to •
- key maintenance components
- Mossy Oak[†] Break-Up Country Camo[†] water dipped option



Mossy Oak Break-Up Country Camo / HD10

/ CA

CĽ

120 x 62 x 78 in

MENSIONS

I v W v H

ENGINES	HD10			
Туре	72 hp, Rotax 976 cc, V-twin, liquid cooled			
Fuel Delivery System	Intelligent Throttle Control (iTC \space^{\space}) with Electronic Fuel Injection (EFI)			
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P			
Drive Train	True 4-mode traction system: 2x4 open rear dif., 2x4 locked rear dif., 4x4 open rear dif., 4x4 locked rear dif. Visco-Lok QE auto-locking front dif.			
Driving Assistance	Electronic Hill Descent Control ECO / Work / Normal modes			
Power Steering	Dynamic Power Steering (DPS)			
SUSPENSIONS				
Front Suspension	Double A-arm / 10 in. (25.4 cm) travel			
Front Shocks	Twin tube gas charged shocks			
Rear Suspension	TTA-HD with external sway bar / 10 in. (25.4 cm) travel			
Rear Shocks	Twin tube gas charged shocks			
BRAKES				
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers			
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers			

LXWXH	120 x 62 x 78 in. (305 x 157.5 x 198.1 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	11 in. (28 cm)
Estimated Dry Weight	1,550 lb (703 kg)
Cage	ROPS-approved profiled cage. Certified ISO 3471 and OSHA.
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.2 gal (61.3 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Central dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Central armrest and holders: 0.9 gal (3.5 L)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

TIRES / WHEELS

Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm) Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)	
Rear Tires		
Wheels	14 in. Black Cast Aluminum	

FEATURES			
	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, ECO / Work / Normal modes, seat belt, diagnostics, clock, auto shut off	Lighting	140-W lighting output from four 35-W reflectors ensuring a wide visiblity, plus LED tail lights with halo glow effect
		Winch	4,500-lb (2,041 kg) winch with roller fairlead
		Seat	VERSA-PRO bench seat with passenger seats flipping up, adjustable driver seat, underside hooks, reinforced XT seat skin and contoured bench to improve entrance/exit of the cab
Battery	12 V (30 amp/h)	Protection	Integrated front steel bumper, full skid plate, full hard roof
Magneto	650 W	Hitch Type	2-in. hitch receiver

Adjustable tilt steering

/ARRANT\

Instrumentation

Factory

2-year limited warranty

Steering Wheel

©2015 Bombardier Recreational Products wc (BRP). All rights reserved. TM, [®] and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP USh. Inc. "Base model dry weight shown. ^{TV}/sco-1 ak is a trademark of GRV Viscodrive GmbH. ^T/All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation. BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsible, BRP highly recommends that all SSV drivers take a training course. SSVs can be hazardous to operate. For your safety: the operator and passengers should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. "Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with hengine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. In some countries models available might be slightly different than models depicted due to regulations provingements. requirements.

Two lighter type DC outlets, one in the console

(20-A) and one in the under dash storage (20-A)



Can-AmOffroad.com